

SAFETY DATA SHEET

According to Work Health and Safety Regulations 2011 and National Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals

Version 1.1

Issue date: 18/09/2019

Revision date: 18/09/2019 SDS Record Number: CSSS-TCO-010-117289

1. Identification of the material and supplier

TULUX CF/SF 40 Diesel Engine Oil Material name:

Other means of identification:

Recommended use: Can be used in gasoline/diesel engine for lubricating, cooling and airproofing etc.

Restrictions on use:

Manufacturer:

Supplier(Manufacturer): SINOPEC LUBRICANT CO.,LTD

Address: No. 6 Anning Zhuang West Road, Haidian District, Beijing, P.R.China

Contact person(E-mail): csc.lube@sinopec.com

Telephone: 86-800-810-9886 Fax: 86-10-82410856 **Emergency number:** 86-800-810-9886

Australia Supplier(Manufacturer): International Lubricant Distributors Pty. Ltd.

Address: Level 3, 43 Kishorn Road, Applecross, 6153 Australia

Contact person(E-mail):

Telephone:

Fax: +61 8 9381 1788 1300 558 939 **Emergency number:**

Waitomo Lubricants Limited (GST 104255744) New Zealand Supplier(Manufacturer):

Address: 15 Ellis Street, Frankton, Hamilton, PO Box 5125, Hamilton 3242

Telephone: +64 7 847 0829 +64 7 846 0032 Fax:

+64 7 847 0829 (24 Hrs) **Emergency number:**

New Zealand Supplier(Manufacturer): MTS ENERGY LTD

Address: 44 Northcote Road, North Shore, Auckland 0627, New Zealand

Telephone: +64 9 480 8921 Fax: +64 9 480 8398

Emergency number: 0800 399 993 (24 Hrs)

New Zealand Supplier(Manufacturer): Ixom Operations Pty Ltd (Incorporated in Australia)

NZBN: 9429041465226

Address: 166 Totara Street, Mt Maunganui South, New Zealand

Contact person(E-mail):

Telephone: +64 9 368 2700 Fax: +64 9 368 2710

Material name: TULUX CF/SF 40 Diesel Engine Oil SDS Australia&New Zealand Version #: 1.1 Issue date: 18-09-2019. Revision date: 18-09-2019. 1/9



Emergency number: 0 800 734 607 (ALL HOURS)

2. Hazards identification

Australia:

Not classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

New Zealand:

Not classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

GHS label elements:

Hazard Pictograms: : No hazard pictogram is used.

Signal word: No signal word is used.

Hazard statement: Not applicable.

Precautionary statement:

Prevention:
Response:
Not applicable.
Storage:
Not applicable.
Not applicable.
Not applicable.
Not applicable.
Not applicable.
Not applicable.

classification:

3. Composition/information on ingredients

Components	CAS No.	Percent
Base oil	64742-44-5	80-90%
Additive	Mixture	<20%

4. First aid measures

Inhalation:No specific first aid measures are required. If exposed to excessive levels of material in

the air, move the exposed person to fresh air. Get medical attention if coughing or

respiratory discomfort occurs.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if

contaminated. To remove the material from skin, use soap and water. Discard

contaminated clothing and shoes or thoroughly clean before reuse.

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if

worn, and flush eyes with water.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get

medical advice.

Symptoms caused by exposure: Not available.

Medical Attention and Special Treatment: Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Extinguishing media which must not be Water.

Material name: TULUX CF/SF 40 Diesel Engine Oil
Version #: 1.1 Issue date: 18-09-2019. Revision date: 18-09-2019.

SDS Australia&New Zealand



used for safety reasons:

Specific hazards arising from the chemical:

This material will burn although it is not easily ignited. Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

Special protective equipment and precautions for fire fighters:

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapors or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid build up of vapor. Ensure sufficient supply of air. Avoid contact with eyes or skin. Contact with water - danger of sliding. Wear appropriate personal protective equipment and clothing to prevent exposure. Increase ventilation. Evacuate all unprotected personnel.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

Stop the source of the release if you can do it without risk. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

7. Handling and storage

Precautions for safe handling:

Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Conditions for safe storage, including any incompatibilities:

Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

Storage regulation

Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well-ventilated area away from naked flames, sparks and other sources of ignition.

8. Exposure controls/personal protection

Control parameters – exposure

Not available

standards, biological monitoring:

Exposure Levels

Material name: TULUX CF/SF 40 Diesel Engine Oil
Version #: 1.1 Issue date: 18-09-2019. Revision date: 18-09-2019.



Occupational exposure limits:

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)						
Components	Туре	Value	Form			
Not available.	Not available.	Not available.	Not available.			
Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)						
Components Type		Value	Form			
Not available.	Not available.	Not available.	Not available.			

No exposure standards have been established for this material.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Appropriate engineering controls: Provide sufficient ventilation to keep airborne levels as low as possible. Where vapours or

mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a

local exhaust ventilation system is required.

Personal protective equipment:

Eye/face protection: No special eye protection is normally required. Where splashing is possible, wear safety

glasses with side shields as a good safety practice.

Skin protection: No special protective clothing is normally required. Where splashing is possible, select

protective clothing depending on operations conducted physical requirements and other

substances in the workplace.

Respiratory protection: No respiratory protection is normally required. No respiratory protection is ordinarily

required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material...If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in

circumstances where air-purifying respirators may not provide adequate protection.

Hand protection: Suggested materials for protective gloves include: Neoprene, Nitrile Rubber.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Form: Oily liquid

Color: Transparent, brown

Odor: Odorless or slight odor

Odour threshold:Not availablePH:Not availableMelting point/Freezing point:Not availableBoiling point and boiling range:Not available

Flash point: 250 °C (Open Cup)(typical)

Evaporation rate: Not available
Flammability (solid, gas): Not available
Upper/lower flammability or explosive Not available

limits:

Vapor pressure: Not available

Material name: TULUX CF/SF 40 Diesel Engine Oil

Version #: 1.1 Issue date: 18-09-2019. Revision date: 18-09-2019.

SDS Australia&New Zealand
4 / 9



Vapor density: Not available

Density: 0.80kg/L~0.90kg/L (20°C)

Solubility (H₂O): Insoluble in water. Partition coefficient (n-octanol/water): > 6 (estimated value)

>260°C **Auto-ignition temperature:**

Decomposition temperature: Not available

Viscosity, dynamic: 12.5 mm2/s - 16.3 mm2/s (100°C)

Specific heat value: Not available Not available Particle size: Volatile organic compounds content: Not available Not available % volatile: Saturated vapour concentration: Not available Release of invisible flammable vapours Not available

and gases:

Additional parameters

Not available Shape and aspect ratio: Crystallinity: Not available **Dustiness:** Not available Surface area: Not available Degree of aggregation or agglomeration: Not available Not available Ionisation (redox potential): Biodurability or biopersistence: Not available

10. Stability and reactivity

Reactivity: Stable under recommended transport or storage conditions.

Chemical stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions: May react with strong oxidizing agents.

Conditions to avoid: Incompatible materials. Avoid extreme temperatures, sun exposure, the fire source.

Incompatible materials: Strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition products: A complex mixture of airborne solids, liquids, and gases including carbon monoxide,

carbon dioxide, and unidentified organic compounds will be evolved when this material

undergoes combustion.

11. Toxicological information

Toxicological data:

Acute toxicity:

LD50(Oral, Rat): >5g/kg LD50(Dermal, Rabbit): >5g/kg LC50(Inhalation, Rat): $>10q/m^3$

Acute toxicity:

Base oil (CAS: 64742-44-5)

LD50(Oral, Rat): > 5000 mg/kg bw LD50(Dermal, Rabbit): > 2000 mg/kg bw LC50(Inhalation, Rat): 2.18 mg/L air No data available.

Skin corrosion/Irritation:

Material name: TULUX CF/SF 40 Diesel Engine Oil Revision date: 18-09-2019. Version #: 1.1 Issue date: 18-09-2019.



Serious eye damage/irritation: No data available. Respiratory or skin sensitization: No data available. Germ cell mutagenicity: No data available. Carcinogenicity: No data available. Reproductive toxicity: No data available. No data available. STOT- single exposure: STOT-repeated exposure: No data available. Aspiration hazard: No data available.

Other information This product has no known adverse effect on human health.

Information on routes of exposure

Symptoms related to exposure

No data available.

No data available.

No data available.

Immediate, delayed and chronic health

No data available.

effects from exposure

12. Ecological information

Ecotoxicity:

Acute t	oxicity	Time	Species	Method	Evaluation	Remarks
LC50	N/A	96h	Fish	OECD 203	N/A	N/A
EC50	N/A	48h	Daphnia	OECD 202	N/A	N/A
EC50	N/A	72h	Algae	OECD 201	N/A	N/A

Persistence and degradability: This material is not expected to be readily biodegradable.

Bioaccumulative potential: This material contains components with potential to bioaccumulation.

Mobility in soil: If into the soil, this material will be adsorbed and not flow.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone

creation potential, endocrine disruption, global warming potential) are expected from this

component.

13. Disposal considerations

Safe handling and disposal methods:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Disposal of any contaminated

packaging:

Australia:

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

New Zealand:

Product Disposal

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a combustible substance and therefore can be sent to an approved high temperature incineration plant for disposal. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply



with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. Transport information

Australia:

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

New Zealand:

Not classified as Dangerous Goods for transport according to the NZS 5433:2012 Transport of Dangerous Goods on Land.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

U.N. Number

None Allocated

Proper Shipping Name

None Allocated

DG Class

None Allocated

Packing Group

None Allocated

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

Australia:

Not classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia.

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

New Zealand:

Not classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

Australia HVIC: Listed substance

Not available.

New Zealand Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations a location test certificate is required when quantity greater than or equal to those indicated below are present.

Material name: TULUX CF/SF 40 Diesel Engine Oil

Version #: 1.1 Issue date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand
7 / 9



Hazard Class

Quantity beyond which controls apply
for closed containers

Not Applicable

Quantity beyond which controls apply
when use occurring in open containers

Not Applicable

Not Applicable

New Zealand Approved Handler

Inventory status

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance Quantities

Not Applicable Not Applicable

inventory status.		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Not available.
Canada	Domestic Substances List (DSL)	Not available.
Canada	Non-Domestic Substances List (NDSL)	Not available.
China	Inventory of Existing Chemical Substances in China	Not available.
	(IECSC)	
Europe	European Inventory of Existing Commercial Chemical	Not available.

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) Not available.

Japan Inventory of Existing and New Chemical Substances Not available.

(ENCS)

Korea Existing Chemicals List (ECL) Not available.

New Zealand Inventory Not available.

Philippines Philippine Inventory of Chemicals and Chemical Not available.

Substances (PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Not available.

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Indication of changes: Version 1.1

Date of preparation or review: 2019.9.18

Key abbreviations or acronyms CAS: Chemical Abstracts Service used: LC50: Lethal Concentration 50

EC50: Concentration for 50% of maximal effect

LD50: Lethal dose 50%

MAC: maximum allowable concentration, MAC)

PC-TWA: permissible concentration-time weighted average PC-STEL: permissible concentration-short term exposure limit

reference Australia:

Standard for the Uniform Scheduling of Medicines and Poisons.

Approved criteria for classifying hazardous substances [NOHSC: 1008(2004)].

National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:

2011(2003)].

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Material name: TULUX CF/SF 40 Diesel Engine Oil

Version #: 1.1 Issue date: 18-09-2019. Revision date: 18-09-2019. 8 / 9

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)



Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work Australia.

American Conference of Industrial Hygienists (ACGIH)

New Zealand:

Workplace Exposure Standards and Biological Exposure Indices

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 0906).

Assigning a hazardous substance to a group standard.

American Conference of IndustriaLHygienists (ACGIH)