

Product	Sinopec ATF 4M-LV Automatic Transmission Fluid
Summary	Product description Sinopec ATF 4M-LV Automatic Transmission Fluid is a multifunctional fluid formulated with high viscosity index base oils and selected additives. It is suitable for use in Multi-Vehicle automatic transmission and hydraulic systems, especially 6~8 AT.

Applications

Sinopec ATF 4M-LV Automatic Transmission Fluid is suitable for:

- Lubrication of automatic transmission and hydraulic systems, especially 6~8AT.

Features and benefits

- Outstanding friction properties to effectively prevent the transmission shudder.
- Excellent low temperature fluidity and shear stability.
- Excellent protection against rust and corrosion, effectively extending the service life of the automatic transmission.
- Effectively control the oil oxidation and deposit formation, keeping transmission system clean.
- Multiple excellent characteristics ensure smooth shift and driving experience.

Product Data Sheet

Typical data

Sinopec ATF 4M-LV Automatic Transmission Fluid		
Property	Typical data	Test Method
Colour	Red	ASTM D 1500
Kinetic viscosity (100°C), mm ² /s	6.02	ASTM D 445
Low temperature viscosity (−30°C), mPa.s	3381	ASTM D 2983
Low temperature viscosity (−40°C), mPa.s	12960	ASTM D 2983
Flash point (COC), °C	206	ASTM D 92

These data are given as an indication of typical values, not exact specifications.

Industry and OEM specifications

Sinopec ATF 4M-LV Automatic Transmission Fluid meets the performance requirements of the following industry and OEM specifications:	
JASO	M315 1A-LV
GM	DEXRON VI
Ford	MERCON V , MERCON LV
Aisin	JWS 3309 (T-IV), AW-1
Toyota	T-IV, WS
Honda	ATF Z-1, DW-1 (except in CVTs)
Mazda	ATF M-III, M-V, FZ
Mitsubishi	Diaqueen SP-II/SP-III, PA
Hyundai/Kia	SP-III ,SP-VI, NWS-9638
Nissan	Matic C,D,J,S
Allison	C-3 & C-4
Chrysler	ATF+, +2, +3, +4
MB	MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9
ZF	TE-ML 09, 11A, 11B, ZF Lifeguard Fluid 6

Sinopec ATF 4M-LV is **not** recommended for where ATF TYPE F/G specification is required.

It should **not** be used in CVT/DCT.

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

Product Data Sheet

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

Issued: October 2020

© Sinopec 2020