

Product	Sinopec MTF 75W-90 Transmission Fluid
Summary	Product description Sinopec MTF 75W-90 Transmission Fluid is formulated with mineral base oils, and an advanced multifunctional additive system. It provides outstanding performance in manual transmissions where excellent synchroniser performance is required. This API GL-4 quality product meets the requirements of many manual transmission manufacturers.

Available sizes



PAIL – 20L



DRUM – 200L



IBC – 1000L

Also
available
in bulk

Applications

Sinopec MTF 75W-90 Transmission Fluid is suitable for use in:

- Manual transmissions with synchronisers.
- Manual transmissions that require an API GL-4 quality oil.
- Manual transmission of many vehicle manufacturers.

Features and benefits

- Excellent synchroniser performance makes gear shifting smoother and quieter, and improves the driving experience.
- Optimised frictional properties and excellent power transmission, ensure that outstanding vehicle fuel economy is achieved.
- Excellent extreme pressure and antiwear performance prevent gear wear, prolong service life and increase maintenance intervals.
- Excellent thermal and oxidation stability reduce the formation of deposits that could damage the gearbox, and ensure long fluid service life.
- Very low pour point ensures fluidity at low temperatures and provides easier cold-start performance in synchronised transmissions.
- Resistance to rust and corrosion ensures protection of the gears and synchroniser, and extends gearbox life.

Product Data Sheet

Typical data

Sinopec MTF 75W-90 Transmission Fluid	
Colour, visual	Brown
SAE grade	75W-90
Kinematic viscosity, ASTM D 445	
cSt @ 40°C	86.4
cSt @ 100°C	15.1
Brookfield Viscosity, ASTM D 2983	
cP @ -40°C	95000
Viscosity index, ASTM D 2270	185
Pour point, °C, ASTM D 97	-42
Flash point (COC), °C, ASTM D 92	220
Density @ 20°C, kg/l, ASTM D 4052	0.864

These data are given as an indication of typical values and not as exact specifications.

Industry and OEM specifications

Sinopec MTF 75W-90 Transmission Fluid meets the performance requirements of the following specifications:	
API Service Classification	Gear lubricant: GL-4

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected in Australia.

Issued: February 2021

© Sinopec 2021